

# 60 HZ DIESEL GENERATOR

FOR INDUSTRIAL PURPOSE

## 22KW



### OUTPUT POWER

Standby Power (ESP)	kVA	28
	kW	22
Rated Power (NG)	kVA	25
	kW	20

SIZE	W x L x H (mm)	Weight (kg)	Fuel Tank (kg)	Fuel Consumption 100% load
Silent Type	2100X930X1300		51	6.4(lt/h)
Open Type	1500X700X1200		51	6.4(lt/h)

### OUTPUT POWER

The maximum power which a generating set is capable of delivering continuously whilst supplying a constant electrical load. Average load can be 100%. The generator must not be overloaded.

### STANDBY POWER

The max power available during a variable electrical power sequence, under the stated operating conditions, for which a generating set is capable of delivering in the event of a utility power outage or under test conditions for up to 200 hrs of operation per year under average of 70% load. Overloading isn't permissible.

### PRIME POWER

The maximum power which a generating set is capable of delivering continuously whilst supplying a variable electrical load. Average load should be 70%. The generator can be overloaded 10% for 1 hour per 12 hrs.



[www.energybak.com](http://www.energybak.com)

# Energybak

## 60 HZ DIESEL GENERATOR

FOR INDUSTRIAL PURPOSE

22KW

## ENGINE

Manufacturer	CUMMINS	
Model	4B3.9-G11	
Cylinder Configuration	Inline	
No of Cylinders	4-In Line	
Engine Power-Standby	25	
Engine Power-Prime	23	
Engine Speed	1800	
Structural Form	Four Stroke	
Speed / Frequency 60Hz	60Hz	
Displacement	3.9	
Bore	1 02	
Stroke	120	
Compression Ratio	18:0:1	
Governor Type	Electronic	
Aspiration	Naturally Aspirated	
Combustion System	Direct Injection	
Cooling System	Water Cooled	
Lubrication Oil Capacity	lt	10.9
Coolant Capacity	lt	27
Fuel Tank Capacity	lt	51
Fuel Consumption %100 60Hz	lt/h	6.4
Fuel Consumption %75 60Hz	lt/h	4.6
Fuel Consumption %50 60Hz	lt/h	3.4

## ALTERNATOR 184E

No of Phases	Three	
Power Factor	0.8	
No of Bearings	Single	
No of Poles	4	
Insulation Class	H	
Degree of Protection	IP23	
Stator Winding	Double Layer Concentric	
Winding Pitch	Two thirds	
Winding Leads	12	
Maximum Overspeed	2250 Rev/Min	
Excitation System	AVR(AutomaticVoltageRegulator), Brushless	
Waveform Distortion	No load < 1.5% Non-Distorting Balanced Linear Load < 5.0%	
R.F.1. Suppression	BS EN 61000-6-2 & BS EN 61000-6-4, VDE 0875N.	

INCLUYE PRECALENTADOR DE REFRIGERANTE Y LUBRICANTE


[www.energybak.com](http://www.energybak.com)
**Energybak**